

Statistical by Putra Wisnu
From publikasi (Publikasi)

Processed on 16-Jun-2023 16:14 WIB
ID: 2117210196
Word Count: 2717

Similarity Index		Similarity by Source	
6%		Internet Sources:	2%
		Publications:	5%
		Student Papers:	5%

sources:

- 1

2% match (student papers from 06-Apr-2023)

[Submitted to Telkom University on 2023-04-06](#)
- 2

1% match (Muhammad Amin Bakri, Ahmad Faizal, Seta Samsiana, Eki Ahmad Zaki Hamidi. "Implementation of Arduino-Based Body Temperature and Olfactory Detector Automatic Door", 2022 IEEE 8th International Conference on Smart Instrumentation, Measurement and Applications (ICSIMA), 2022)

[Muhammad Amin Bakri, Ahmad Faizal, Seta Samsiana, Eki Ahmad Zaki Hamidi. "Implementation of Arduino-Based Body Temperature and Olfactory Detector Automatic Door", 2022 IEEE 8th International Conference on Smart Instrumentation, Measurement and Applications \(ICSIMA\), 2022](#)
- 3

1% match (Eki Ahmad Zaki Hamidi, Syaiful Ahdan, Jupriyadi, Adi Sucinto, Hasan Nur Arifin, Nana Rachmana Syambas. "Load Balancing on Named Data Networking, Case Study: UIN Topology in Indonesia", 2022 16th International Conference on Telecommunication Systems, Services, and Applications (TSSA), 2022)

[Eki Ahmad Zaki Hamidi, Syaiful Ahdan, Jupriyadi, Adi Sucinto, Hasan Nur Arifin, Nana Rachmana Syambas. "Load Balancing on Named Data Networking, Case Study: UIN Topology in Indonesia", 2022 16th International Conference on Telecommunication Systems, Services, and Applications \(TSSA\), 2022](#)
- 4

1% match ("Table of Content", 2022 16th International Conference on Telecommunication Systems, Services, and Applications (TSSA), 2022)

["Table of Content", 2022 16th International Conference on Telecommunication Systems, Services, and Applications \(TSSA\), 2022](#)

paper text:

4Statistical and Spectral Feature Extraction of Oryzias Celebensis Heart Rate
Putra Wisnu Agung Sucipto

Electrical Engineering Department Universitas Islam “45” Bekasi,

3Indonesia 2022 16th International Conference on Telecommunication
Systems, Services, and Applications (TSSA) | 978-1-6654-5594-7/22/\$31.00
©2022 IEEE | DOI: 10.1109/TSSA56819.2022

.10063878 wisnu@unimabekasi.ac.id Setyo Supratno Electrical Engineering Department Universitas Islam “45” Bekasi, Indonesia setyo@unismabekasi.ac.id Khusnul Yaqin Fisheries Department Universitas Hasanuddin Makasar, Indonesia khusnul@unhas.ac.id Annisa Firasanti Electrical Engineering Department Universitas Islam “45” Bekasi, Indonesia annisa_firasanti@unismabekasi.ac.id Abstract—Due to its unique

characteristics, the heart rate of *Oryzias Celebensis* can play an important role in the observation of the health of the aquatic environment. Unfortunately, due to its tiny size, the process of scanning the heart rate of these fish fry requires sophisticated device engineering. The purpose of this study is to extract cardiac signal characteristics of *Oryzias Celebensis* seeds based on statistical and spectral aspects. We performed the extraction of statistical and spectral characteristics of heart rate using five statistical formulas namely mean, variance, standard deviation, skewness and kurtosis. As for spectral characteristic, we analyze the magnitude value of the discrete Fourier transformation from the color intensity that appear in the video view. The results of this study showed that statistical characteristic has much better result with 50% accuracy of pulse calculations while spectral characteristic that use fourier transformation only shows 0.2% accuracy.

Keywords—*Oryzias Celebensis*, Heart rate, Video Processing, Feature Extraction

I. INTRODUCTION

The unique characteristics of *Oryzias* fish seeds have make this species own an advantages for the benefit of research and experimentation on the health of the aquatic environment. Aside from having a complete genome sequence, *Oryzias* also has a high fecundity, a transparent body, and is adaptive to various temperatures. That's why these fish are often used as a marker of the health of the surrounding environment. Healthy aquatic environment, characterized by the preservation of the state of health of these fish and vice versa [1]. One of the vital organ that indicate the health of fish seeds is heart rate. The heart pumps bloodstream in the body, pulsates in a certain range of values per minute. The range of its pulsation will depend on the state of health of the seeds which strongly connected with the situation of surrounding aquatic environment[2]. Unfortunately, due to its tiny size—approximately 2 millimeters long— the process of heart rate scanning of these fish seeds requires sophisticated device. This heart rate monitoring has been done by many researchers indeed. Heart rate can be observed by the installation of sensors inside the fish body [3][4], anesthesia [5], based on radar antennas [6] and non-boxed camera-based[7]. The calculation of the pulse is performed based on the calculation of the electrocardiogram signal and the extraction of the digital

Muhammad Amin Bakri

2Electrical Engineering Department Universitas Islam “45” Bekasi, Indonesia
amin@unismabekasi.ac.id Eki Ahmad Zaki Hamidi Electrical Engineering
Department UIN Sunan Gunung Djati Bandung Bandung, Indonesia
ekiahmadzaki@uinsgd.ac.id

image signal which contains variations in the intensity of light when the pulsation occurs. Observation of digital image signals in order to extract a feature mostly done using signals in the time or frequency domain. It is not uncommon that in its processing, the statistical analysis is also involved as a series of feature observations[8][9][10][11][12]. Spectral feature-based feature extraction typically uses frequency spectrum processing in signals [12] [13][14][15][16][17]. This study is focused on making observations to extract heart signals of *Oryzias Celebensis* seeds based on statistical and spectral aspects. The extraction is performed using 5 statistical characteristics: mean, variance, standard deviation, skewness and kurtosis. We observed spectral feature extraction using discrete fourier transformations to see the magnitude of the fourier coefficients of 256 color classes, ranging from white to black and the color classroom between the two.

II. RESEARCH METHOD

The study was conducted in several stages. We started by taking a video showing footage of the heart rate of *Oryzias Celebensis* seeds. The recording process uses a camera of Vivo 7 with Octa-core 1.8 GHz Cortex-A53 Qualcomm SDM450 Snapdragon 450 processor and 4 GB RAM. This smartphone is attached to the microscope and video has been enlarged 6 times and 40 times from microscope. The video views of this recording are processed frame by frame. We only use the color intensity of pixels in the image to observe the characteristics of the heart rate. The color intensity of every pixel is taken and collected together to be extracted into characteristic of a pulsation. This extraction process use the provisions of statistical theory includes mean, variance, standard deviation, skewness and kurtosis. The mean needs to be calculated because it can show the average texture surface of the object. The surface aspect can be strengthened by the distribution of data of variance in a data center indicated by the standard deviation value. The distribution of these data centers can also be shown in terms of membership based on skewness and kurtosis. In addition to statistical features, we also extracted spectral features in each frame using the fourier transform as described by the equation (1).

978-1-6654-5594-7/22/\$31.00 ©2022 IEEE

..... (1) where, A_k = Value of discrete fourier transformation n = amount of data m = mth pixel m = index of pixel k = observation frequency (a) (b) Based on this transformation, the image of the heart rate in the frame was studied from the point of view of the frequency of color intensity per pixel using the fourier transformation magnitude value of each pixel. The expectation is that with this magnitude value, when a pulsation occurs, there will be a distinctive pattern of the pulsation heart chambers based on the intensity of the overall frequency of pixel colors in the image in the frame. (c) (d) Based on the characteristics that have been extracted, we mark the presence and absence of a pulsation that occurs. If there is a pulsation, then the statistical feature is represented in a different sign than when there is no pulsation. Simultaneously with this process, calculations of the accuracy and precision of pulsations are also carried out. The calculation of the pulse and matching of the representation of this pulsation mark is performed using hands and eyes without the help of a computer. III. RESULTS AND DISCUSSION (e) We have record this seed heart rate and taken a string of Fig. 2. Statistical data characteristic based on (a) Mean, (b) Varians, (c) Standar Deviasi, (d) Skewness dan (e) Kurtosis frames in size 240x240 pixels, as shown in figure 1. The area of the heart chambers appears on the pixels shrouded by a green box. The situation when the chambers that the heart is Referring to figure 2, the dynamics of the color intensity in a deflating state appear in figure 1.a, and vice versa in figure values in the frame is wide-ranging. Variance values that show 1.b the chambers of the heart are in an expanding state. variations in intensity values along the frame strands is fluctuating. This condition also looks the same as the standard These frames are initially loaded in the RGB color space, deviation, skewness and kurtosis values. However, it is the then converted into grayscale. Then, this grayscale image is opposite with a mean value that tends to be flat/fixed. The calculated the statistical values of mean, variance, standard mean value in the frame strand tends not to be able to indicate deviation, skewness and kurtosis for the overall intensity of the movement of the object of the heart organ in the frame. the color that appears in the frame. This value calculation is applied to 300 frames in a recorded heart of the seed. The The movement of the heart chambers during the process characteristics of the data, shown in figure 2. of pumping blood in the pulsation record is strongly indicated by the presence of standard values of deviation, skewness and kurtosis, compared to the mean. Although the focus of the study was only on the chambers, but because the blood was also recorded moving, both are integrated into a single set of statistical characteristics that indicate the presence of chamber movements. Fig. 1. Heart Chamber when (a) Deflated and (b) expand (a) (b) (c) Fig. 3. The simultaneity between chamber pulsation and the formation of kurtosis peak shows by (a) Kurtosis graph with 5 peak when the chamber expand; (b) chamber expansion in frame 1, 16, 35, 49 and 65; (c) chamber deflation at 2-3 frame before the expansion in frame 1, 16, 35, 49, 65. Intensity data in the frame that fluctuated is in line with the occurrence of pulsations when blood was flowed. Indications of the presence of pulsations arise clearly along with fluctuations in the value of kurtosis. Whenever the chamber expands, the kurtosis value forms the peak of its value graph, and begins to slowly form a slope as the heart chamber deflates. The simultaneity between the expanding chamber and the formation of graph peaks is not visible in other statistical characteristic: mean value, skewness, variance and standard deviation. An illustration of this incident appears in figure 3, which records the strings of frames number 1 through number 35. In this strand, there are 5 expansions of the heart chambers, which is accompanied by the generation of 5 peaks of kurtosis. In the same strand, the variance value and the standard deviation show the formation of peaks similar to kurtosis. There are 5 peaks on the chart, just like what happens on the kurtosis chart. Thus, when viewed visually, variance and standard deviation seem to give the same response as kurtosis when expansion and deflation of chambers occur. However, if you look at it in more detail, there are differences that need to be considered. By the time the peak of kurtosis begins to be maximum, it turns out that no peaks are formed at standard deviations and variances. Then, when the peak of kurtosis begins to fall, the standard deviation begins to prepare for the formation of the peak. This condition shows that standard deviations and variances are less dominant in indicating the presence of a heart. An illustration of the peak position in the kurtosis chart, standard deviation and variance in the frame strands related to this condition is shown in figure 4. (a) (b) (c) Fig. 4. The position of peak appearance in first 70 frame; (a) Kurtosis Graph, (b) Standar deviasi, dan (c) Variansi When viewed from a spectral aspect, the presence of heart rate in the magnitude of the image frequency resulting from the fourier transformation has distinctive characteristics that are different from the statistical aspect. Based on the results of the fourier transformation, the variation in the magnitude in image pixels in frames 1, 16, 35, 49 and 65 appears to be variative. An illustration of the image resulting from this fourier transformation can be seen in figure 5. (a) (b)

Fig. 5. Image of heart rate based on Fourier Transform, (a) chamber expansion in frame 1, 16, 35, 49 and 65; (b) chamber deflation at 2-3 frame before the expansion in frame 1, 16, 35, 49, 65. Based on figure 5, it can be seen that there is a variation in the diameter of the distribution of low-frequency intensity, which is described in light green areas in a blue circle. Although it varies, this tinge of color does not significantly give a distinctive difference in characteristics. At the time of expansion of the heart chambers and during their deflation, there is no difference in the diameter of the coverage area of the burst which can be used as a strong reference marker of the expansion or shrinkage of the heart chambers. Based on the accuracy of the calculation of the pulse based on statistical and spectral characteristics, the results of the heart rate calculation are more accurate using statistical characteristics than the spectral characteristics based on the fourier transformation. Heart rate measurement using statistical characteristics using kurtosis as a reference for calculating the pulse for 4 video recordings of heart rate in this study showed an accuracy of 50%. Meanwhile, the accuracy of pulse calculations using spectral characteristics based on the magnitude of the light intensity frequency shows an accuracy of 0.2%. The percentage of 50% using statistical features appears to decline when the footage appears dark and tends not to have a rough texture over the surface of the object in the image. Video views with a lot of pixel fluctuation activity tend to be more likely to evoke adequate kurtosis to signal a heart rate. The accuracy value using this kurtosis feature visually appears much better than the spectral feature using the fourier transformation, because it tends not to have a distinctive distribution pattern at the time of the deflation transition to the expansion of the heart chambers.

IV. CONCLUSION This study has succeeded in showing the characteristic in

4

statistical and spectral characteristics of *Oryzias Celebensis* heart rate

. Statistical characteristics that can be used as pulse markers are standard deviation, variance and kurtosis. Of the three, kurtosis shows strong evidence that can be used as the main marker of a pulsation. On the other hand, the mean and skewnes have not found strong evidence to be used as a pulse characteristic. Same thing happen as the magnitude characteristic of the frequency of light intensity in pixels in the image resulting from the fourier transformation.

REFERENCES [1] I. Ashary, A. K. B, and K. Yaqin, “Pengaruh Paparan Logam Timbal Terhadap Kematian Embrio Ikan Medaka Embrio (*Oryzias Celebensis* Weber , 1894) di Indonesia Effect of Lead Exposure on Embryonic Mortality of Medaka Fish (*Oryzias Celebensis* Weber , 1894) in Indonesia SIGANUS : Journal of ,” vol. 3, no. 2, 2022. [2] Risnawati, M. R. Umar, and I. Andriani, “Distrbusi Populasi Dan Ekologi Ikan Medaka *Oryzias* spp. di Perairan Sungai Maros, Kabupaten Maros Sulawesi Selatan,” Univ. Hasanuddin, pp. 1–9, 2015. [3] [4] Y. Shen et al., “Estimating Heart Rate and Detecting Feeding Events of Fish Using an Implantable Biologger,” pp. 37–48, 2020. Y. Shen et al., “In-situ Fish Heart-rate Estimation and Feeding Event Detection Using an Implantable Biologger,” vol. 1233, no. c, pp. 1–15, 2021. [5] T. Le et al., “Continuous Electrocardiogram Monitoring in Zebrafish with Prolonged Mild Anesthesia,” Proc. Annu. Int. Conf. IEEE Eng. Med. Biol. Soc. EMBS, vol. 2020-July, pp. 2610–2613, 2020. [6] N. Hafner, J. C. Drazen, and V. M. Lubecke, “Fish heart rate monitoring by body-contact Doppler radar,” IEEE Sens. J., vol. 13, no. 1, pp. 408–414, 2013. [7] [8] [9] E. Puybureau, H. Talbot, and L. Marc, “Automated heart rate estimation in fish embryo,” pp. 379–384, 2015. J. Zhang, X. Wu, Y. Yu, and D. Luo, “A Novel Method of Feature Extraction and,” vol. 0, no. 2, 2012. J. Yang and J. Guo, “Image Texture Feature Extraction Method Based on Regional Average Binary Gray Level Difference Co-occurrence Matrix,” pp. 1–4, 2011. [10] Q. Wang, W. Huang, X. Niu, and X. Jiang, “A statistic feature-based scheme for the template protection of 2D face recognition,” pp. 374– 377, 2008. [11] R. Karthika, “An Efficient Feature Subset Selection for Improved Stability using T-Statistic,” pp. 326–329, 2017. [12] X. Jiang, “Cavitation Noise Classification Based on Spectral Statistic Features and PCA Algorithm,” pp. 438–441, 2013. [13] K. Phromsuthirak and V. Areekul, “Fingerprint Quality Assessment Using Frequency and Orientation Subbands of Block-based Fourier Transform,” 2013. [14] T. Dzanic and F. D. Witherden, “Generated Images,” no. NeurIPS 2020, pp. 1–11. [15] C. Menzel, G. U. Hayn-leichsenring, O. Langner, and H. Wiese, “Fourier Power Spectrum Characteristics of Face Photographs : Attractiveness Perception Depends on Low-Level Image Properties,” no. Study 3, pp. 1–27, 2015. [16] A. Dutta, Chapter 4 - Fourier Transform Infrared Spectroscopy. Elsevier Inc., 2017. [17] K. Chandrasegaran, “A Closer Look at Fourier Spectrum Discrepancies for CNN-generated Images Detection,” pp. 7200–7209.

1 Authorized licensed use limited to: Universitas Indonesia. Downloaded on March 30,2023 at 07:19:51 UTC from IEEE Xplore. Restrictions apply.
Authorized licensed use limited to: Universitas Indonesia. Downloaded on March 30,2023 at 07:19:51 UTC from IEEE Xplore. Restrictions apply.
Authorized licensed use limited to: Universitas Indonesia. Downloaded on March 30,2023 at 07:19:51 UTC from IEEE Xplore. Restrictions apply

. Authorized licensed use limited to: Universitas Indonesia. Downloaded on March 30,2023 at 07:19:51 UTC from IEEE Xplore. Restrictions apply.